



| MODEL | PIPE SIZE | DN | TEMP. RANCE | MAX. PRESSURE | WEIGHT |
|-----------|-----------|----|--------------------------------|----------------|---------------------|
| SLFM S 25 | 1" | 25 | -23°C(-10°F) to +66°C (+150°F) | 6 bar / 87 PSI | 0,968 lb / 0,440 kg |

| Material | Min. Turning Effort | Min. Bending Moment | CV | Eqv Lenght of pipe (ft) |
|-------------------------------------------|-----------------------|---------------------|----|-------------------------|
| Aluminium Alloy / Brass / Stainless Steel | 750 Inc lbf / 84,7 Nm | 32,0 Lb / 14,5 kg | 10 | 2.5 |

FLOW CAPACITY TABLE IWC/PSIG - Capacity S.C.F.H

| Pressure Drop | | Inlet Pressure (iwc) | | Inlet Pressure (psi) | | | | | |
|---------------|-----|----------------------|---------|----------------------|------|------|------|------|------|
| psi | iwc | 8" iwc | 14" iwc | 3 | 5 | 7 | 10 | 20 | 60 |
| 0.0036 | 0.1 | 169 | 170 | 183 | 193 | 203 | 216 | 257 | 376 |
| 0.0072 | 0.2 | 238 | 240 | 259 | 273 | 287 | 306 | 363 | 532 |
| 0.0108 | 0.3 | 292 | 294 | 317 | 335 | 351 | 375 | 444 | 652 |
| 0.0144 | 0.4 | 337 | 340 | 366 | 387 | 406 | 433 | 513 | 753 |
| 0.018 | 0.5 | 377 | 380 | 410 | 432 | 454 | 484 | 574 | 842 |
| 0.0216 | 0.6 | 413 | 416 | 449 | 473 | 497 | 530 | 628 | 922 |
| 0.0252 | 0.7 | 446 | 449 | 485 | 511 | 537 | 572 | 679 | 996 |
| 0.0288 | 0.8 | 477 | 480 | 518 | 546 | 574 | 612 | 725 | 1065 |
| 0.0324 | 0.9 | 505 | 509 | 549 | 580 | 608 | 649 | 769 | 1129 |
| 0.036 | 1.0 | 533 | 536 | 579 | 611 | 641 | 684 | 811 | 1190 |
| 0.072 | 2.0 | 752 | 796 | 818 | 863 | 906 | 967 | 1146 | 1683 |
| 0.108 | 3.0 | 920 | 927 | 1001 | 1056 | 1109 | 1183 | 1403 | 2061 |
| 0.144 | 4.0 | 1061 | 1069 | 1154 | 1218 | 1279 | 1365 | 1619 | 2379 |
| 0.18 | 5.0 | 1185 | 1194 | 1289 | 1361 | 1429 | 1525 | 1810 | 2659 |

FLOW CAPACITY TABLE IWC/PSIG - Capacity m³/h

| Pressure Drop | | Inlet Pressure (iwc) | | Inlet Pressure (psi) | | | | | |
|---------------|-----|----------------------|---------|----------------------|-------|-------|-------|-------|-------|
| psi | iwc | 8" iwc | 14" iwc | 3 | 5 | 7 | 10 | 20 | 60 |
| 0.0036 | 0.1 | 4,73 | 4,76 | 5,12 | 5,40 | 5,68 | 6,05 | 7,20 | 10,53 |
| 0.0072 | 0.2 | 6,66 | 6,72 | 7,25 | 7,64 | 8,04 | 8,57 | 10,16 | 14,90 |
| 0.0108 | 0.3 | 8,18 | 8,23 | 8,88 | 9,38 | 9,83 | 10,50 | 12,43 | 18,26 |
| 0.0144 | 0.4 | 9,44 | 9,52 | 10,25 | 10,84 | 11,37 | 12,12 | 14,36 | 21,08 |
| 0.018 | 0.5 | 10,56 | 10,64 | 11,48 | 12,10 | 12,71 | 13,55 | 16,07 | 23,58 |
| 0.0216 | 0.6 | 11,56 | 11,65 | 12,57 | 13,24 | 13,92 | 14,84 | 17,58 | 25,82 |
| 0.0252 | 0.7 | 12,49 | 12,57 | 13,58 | 14,31 | 15,04 | 16,02 | 19,01 | 27,89 |
| 0.0288 | 0.8 | 13,36 | 13,44 | 14,50 | 15,29 | 16,07 | 17,14 | 20,30 | 29,82 |
| 0.0324 | 0.9 | 14,14 | 14,25 | 15,37 | 16,24 | 17,02 | 18,17 | 21,53 | 31,61 |
| 0.036 | 1.0 | 14,92 | 15,01 | 16,21 | 17,11 | 17,95 | 19,15 | 22,71 | 33,32 |
| 0.072 | 2.0 | 21,06 | 22,29 | 22,90 | 24,16 | 25,37 | 27,08 | 32,09 | 47,12 |
| 0.108 | 3.0 | 25,76 | 25,96 | 28,03 | 29,57 | 31,05 | 33,12 | 39,28 | 57,71 |
| 0.144 | 4.0 | 29,71 | 29,93 | 32,31 | 34,10 | 35,81 | 38,22 | 45,33 | 66,61 |
| 0.18 | 5.0 | 33,18 | 33,43 | 36,09 | 38,11 | 40,01 | 42,70 | 50,68 | 74,45 |

FLOW CAPACITY TABLE IWC/PSIG - Capacity kW

| Pressure Drop | | Inlet Pressure (iwc) | | Inlet Pressure (psi) | | | | | |
|---------------|-----|----------------------|---------|----------------------|--------|--------|--------|--------|--------|
| psi | iwc | 8" iwc | 14" iwc | 3 | 5 | 7 | 10 | 20 | 60 |
| 0.0036 | 0.1 | 49,92 | 50,22 | 54,06 | 57,01 | 59,97 | 63,81 | 75,92 | 111,07 |
| 0.0072 | 0.2 | 70,31 | 70,90 | 76,51 | 80,64 | 84,78 | 90,39 | 107,23 | 157,15 |
| 0.0108 | 0.3 | 86,26 | 86,85 | 93,64 | 98,96 | 103,69 | 110,78 | 131,16 | 192,60 |
| 0.0144 | 0.4 | 99,55 | 100,44 | 108,12 | 114,32 | 119,93 | 127,91 | 151,54 | 222,44 |
| 0.018 | 0.5 | 111,37 | 112,25 | 121,11 | 127,61 | 134,11 | 142,97 | 169,56 | 248,73 |
| 0.0216 | 0.6 | 122,00 | 122,89 | 132,63 | 139,72 | 146,81 | 156,56 | 185,51 | 272,36 |
| 0.0252 | 0.7 | 131,75 | 132,63 | 143,27 | 150,95 | 158,63 | 168,97 | 200,58 | 294,22 |
| 0.0288 | 0.8 | 140,91 | 141,79 | 153,02 | 161,29 | 169,56 | 180,78 | 214,17 | 314,60 |
| 0.0324 | 0.9 | 149,18 | 150,36 | 162,17 | 171,33 | 179,60 | 191,71 | 227,16 | 333,51 |
| 0.036 | 1.0 | 157,45 | 158,33 | 171,04 | 180,49 | 189,35 | 202,05 | 239,57 | 351,53 |
| 0.072 | 2.0 | 222,14 | 235,14 | 241,64 | 254,93 | 267,63 | 285,65 | 338,53 | 497,16 |
| 0.108 | 3.0 | 271,77 | 273,84 | 295,70 | 311,94 | 327,60 | 349,46 | 414,45 | 608,82 |
| 0.144 | 4.0 | 313,42 | 315,78 | 340,89 | 359,80 | 377,82 | 403,22 | 478,25 | 702,76 |
| 0.18 | 5.0 | 350,05 | 352,71 | 380,77 | 402,04 | 422,13 | 450,49 | 534,67 | 785,47 |

| | |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CERTIFICATES | TUV Austria CE Attestation of Conformity Certificate (EN 12266-1/ EN 12516-3) |
| APPLICATION | Gasses : Natural Gas, LPG, methane, propane, air, etc... non corrosive gaseous fluids. |
| INFORMATION | Experiments were carried out with air. Calculations based on gas with a density of 0.64 and a calorific value of 37 MJ/m ³ . The measured flow value is arranged according to 15 °C and 101.3 kPa pressure. |

